Approved For Release 2002/10/21 GIA-RDP63-00313A000600140040-7

14 00073998D

NRO REVIEW COMPLETED

COR-0725-60

8 January 1960

METORARDUM FOR: Deputy Director (Plans)

THUME

t Acting Chief, DFD

SUBJECT

25X1

: Evaluation of ITEM Proposal For A Follow-On High Acuity Camera

visited ITEX on 16 December 1939 to obtain additional information to aid in evaluation of the proposal. The proposal is for improvement in the C-prime sensors for CORONA. If the proposal is accepted, ITEX then would start delivery of the improved C-prime camera with camera No. 4. Pairohild would deliver the first three (3) cameras in accordance with the present deison. Although ITEX briefly discusses their new environmental test facility, it is not considered part of the proposal and it is understood that funding for the improved facilities are being accomplished by the Air Force under the E-5 portion of System 117L.

- 2. The proposal poses four (A) major improvements to the camera:
 - a. Structure
 - b. Continuelly rotating lens
 - c. We platen
 - d. Elimination of the skewed rollers

It is felt that greatest improvement in the samera is going to be schioved through the new structure shown in attachments one (1) and two (2). Without a doubt this improvement would eliminate many of the alignment problems and would reduce camera weight approximately four (4) pounds. The continually rotating lams, although a desirable feature, would probably be of value only with the present lens design. ITEK has indicated that there is great growth potential in this area and that new and better lenses could be easily installed. However, since the lens must be rotated on the note of emission, and since all lenses rotating in this manner must be mounted accurately at this point, it is questionable whether a different lens could be mounted in such; a manner without considerable change in the camera structure. It should be pointed out, though, that such an installation can be operated at about 1/3 the power requirements with an ultimate savings in overall system weight.



- 3. There is a question if the camera will operate satisfactorily and give the resolution desired without the camera platen. ITEK has schieved 110 lpm in most-up tests at the ends as well as the center of the film forest. Should the camera fail to operate satisfactorily without a platen, this would not be a serious problem since the present platen could be installed without much trouble.
- 4. Elimination of the skewed rollers is a most desirable feature and to accomplish this, ITEE proposes to twist the film 90°, as shown in attachment #3. Film has been operated in the illustrated most-up satisfactorily, but the erose on the twisting rollers must be redesigned to insure proper tension across the face of the film. Should the cross rollers be improporly designed, this could be the cause of opens failure at altitude.
- 5. ITEM proposes to continue to use FCEC as a sub-contractor to supply parts and sub-assembly. Complete camera assembly and testing would be a accomplished at ITEM's facility.
 - 6. The design as proposed does offer several advantages, they are:
 - a. Induction in weight
 - b. Monlicity
 - c. Less emulsion build up within the owners
 - d. Slower film speeds during film retoring cycle
 - e. Klimination of the skewed rollers

ikerror, there are several items on the debit side that seem to make proposed modifications questionable. They are:

- a. It is questionable whether ITEK can complete design, fabricate and test in time to deliver first item on 15 June.
- b. The problem of file twist between the output metering roller and guilletine and the take-un cases to had not been reviewed, and at the time of visit no solution was in eight.

NRO

25X1

c. Since the continually rotating lens, stove pipe, and film are mounted to a single shaft, this might cause a serious vibration problem during operation with a great loss in resolution.

Items 3 and C shove can, without a doubt, be resolved but the effort and time required might effect ITEM's proposed delivery schedule.

7. The proposed modification outlined above would, without a doubt, result in a superior camera for CENTER and ITEE has indicated that increase in costs should not comeed in view of this it is recommended

NRO 25X1

Approved For Release 2002/10/21: CIA-RDP63-00313A000600140040-7

that the prime contractor be given the responsibility to evaluate ITER's proposal and approve the modification only if, they our assure us that they will meet flight achedules as required, and at no additional cost other then that recommended above.

> S/GNED Chief, Development Branch DID-OD/F

25X1

25X1

DF0-30/P

Matribution

- 0 Addresses w/stt
- 2 35/08/0PD, wo/att
- 1 DEVOID, wo/att
- 1 A/Ch/DPD, wo/att 1 EI/DPD, wo/att

Attachaenter

Three platures.